



Tel : 603-42949749  
 Fax : 603-42949759  
[www.lptech.com.my](http://www.lptech.com.my)

## LP Data Digital Display



### BENEFIT:

- : Promotes Healthy Team (Line) Competition or Awareness
- : Indicates Corrective Action Needs.
- : Motivate Staff & Improve Productivity.
- : Real Time Production Information for supervisor & Manager.

### FEATURES:

- : Large & Accurate Super Bright Led Display .
- : Low Maintenance

### APPLICATION:

- : Production Planning & Control.
- : Production Status.

### Specification

No. of Row	One or more
Figure Size	2.3", 4", 6", and 8"
Color of LED	RED, Green, Amber
Digits	2, 3, 4, 5, 6
Interface Protocol	RS232 or RS485 Mitsubishi , Omron, Mobus
Sided of Display	Single Sided or Double Sided
Visibility	2.3" Solid Segment - 60' / 80' 4" Solid Segment - 100' / 140' 6" Discrete - 180' / 240' 8" Discrete - 240' / 320'
Power Source	240VAC or 110VAC $\pm$ 10% 50 Hz
Mounting	Hang or wall Type

Model	Dimension (mm)			
	Led Height	Length	Width	Height
LPD1000-24-S	2.3" 4 digits	246	49	124
LPD1000-44-S	4" 4 digits	412	49	173
LPD1000-24-DS	2.3" 4 digits	264	76	144
LPD1000-44-DS	4" 4 digits	433	76	195

### HOW TO ORDER DATA DISPLAY

LPD1000-AB-CD

Key	Description	Choices
A	Digits Height	2= 2.3" (Solid Digits) 4= 4" (Solid Digits) 6= 6" (Discrete Digits) 8= 8" (Discrete Digits) O= Others
B	Number of digits	2, 3, 4, 5, 6
C	Sided of display	D : Double sided S : Single Sided
D	Display Colour	RED ( Standard ) G= Green A= Amber ( Discrete only )

Eg : Require 4" led 5 digits, Single sided Green Color

**Model : LPD1000-45-S**

### Single Row 4 Digit RS232 communication protocol

<STX><DIGIT 1><DIGIT 2><DIGIT 3><DIGIT 4><DECIMAL PLACE><ETX>

<STX> = 0x02

<DIGIT 1-4> = 0-9 (ASCII)

<DECIMAL PLACE> = 0-4 (ASCII)

<ETX> = 0x03

**We also provide customer with solutions and a variety of customize products Which meet your requirements economically.**

**Please Feel Free to contact us if you have any doubt?**