Release 07/11

Drawing Name LP 24 Hour Clock-D14

Tel: 603-42949749 Fax: 603-42949759 www.lptech.com.my

## LP 24 Hour Digital Clock



#### **BENEFIT:**

- : Create Awareness of Time Management
- : Increase Productivity
- : contemporary digital styling is heighly
- : readable ...... Lending a professional
- : image to any business or organization

#### **FEATURES:**

- : Large & Accurate Super Bright Led Display .
- : Easy Installation.
- : Low Maintenance.

#### **APPLICATION:**

- : Service Department
- : Ware House
- : Hotel / Medical Center


### **Specification**

| <del>Opodiiioa dioii</del> |  |  |  |  |  |
|----------------------------|--|--|--|--|--|
| No. of Row                 | 1 OR 2                                       |  |  |  |  |
| Figure Size                | 2.3", 4", 6", 8", 20" Others                 |  |  |  |  |
| Color of LED               | Red , Green and Amber                        |  |  |  |  |
| Digits                     | 4 or 6                                       |  |  |  |  |
| Sided of Display           | Single Sided or Double Sided                 |  |  |  |  |
| Viewing Distance           | 2.3" Solid Segment - 60' / 80'               |  |  |  |  |
| Recomented /               | 4" Solid Segment - 100' / 140'               |  |  |  |  |
| Maximum                    | 6" Discrete - 180' / 240'                    |  |  |  |  |
|                            | 8" Discrete - 240' / 320'                    |  |  |  |  |
| Power Source               | 230Vac <u>+</u> 10% 50 Hz ( 12v 1.5A Adapto) |  |  |  |  |
| Memory                     | Battery Backup                               |  |  |  |  |
| Mounting                   | Hang Type                                    |  |  |  |  |
| Display                    | HH.MM or HH.MM.SS                            |  |  |  |  |
| Format                     | 12 or 24h                                    |  |  |  |  |
| Accuracy                   | <u>+</u> 2 Minute /Year                      |  |  |  |  |
| Setting                    | Remote Controller                            |  |  |  |  |
|                            |  |  |  |  |  |

### **HOW TO ORDER 24 HOURS CLOCK**

LPT-AB-CD-E

| Key | Description      | Choices   |  |
|-----|------------------|---|--|
| A   | Digits Height    | 2= 2.3" (Solid Digits) 4= 4" (Solid Digits) 6= 6" (Discrete Digits) 8= 8" (Discrete Digits) 20= 20" (Discrete Digits) O= Others |  |
| В   | Number of digits | 4 or 6  |  |
| С   | Sided of display | D : Double sided<br>S : Single Sided  |  |
| D   | Display Color    | R= RED<br>G = Green<br>A = Amber ( Discrete only )  |  |
| Е   | Number of Row    | 1 = One Row<br>2 = 2 Row  |  |







We also provide customer with solutions and a variety of customize products Which meet your requirements economically. Please Feel Free to contact us if you have any doubt?



Release: 07/11

Drawing Name: LP 24 HOUR CLOCK-D14

Tel: 603-42949749

Fax: 603-42949759 www.lptech.com.my

# LP 24 Hour Digital Clock





**Specification** 

| _ •                          |                                       |                           |               |               |               |                           |               |               |  |
|------------------------------|---------------------------------------|---------------------------|---------------|---------------|---------------|---------------------------|---------------|---------------|--|
| Model                        | LPT-24-SR-1                           | LPT-24-SG-1               | LPT-24-DR-1   | LPT-24-DG-1   | LPT-44-SR-1   | LPT-44-SG-1               | LPT-44-DR-1   | LPT-44-DG-1   |  |
| Display                      | Indoor Display                        |                           |               |               |               |                           |               |               |  |
| No. of Row 1                 |                                       |                           |               |               |               |                           |               |               |  |
| Figure Size                  |                                       | 2.3                       | Inch          |               | 4 inch        |                           |               |               |  |
| Color of LED                 | Red                                   | Green                     | Red           | Green         | Red           | Green                     | Red           | Green         |  |
| Digits                       | 4                                     | 4                         | 4             | 4             | 4             | 4                         | 4             | 4             |  |
| Sided of Display             | Single                                | Single Sided Double Sided |               |               |               | Single Sided Double Sided |               |               |  |
| Viewing Distance             | 2.3" up to 25 Meter 4" up to 50 meter |                           |               |               |               |                           |               |               |  |
| Power Source                 | 230VAC <u>+</u> 10%                   |                           |               |               |               |                           |               |               |  |
|                              | 12v 1.5A Adaptor Or 15V Power Supply  |                           |               |               |               |                           |               |               |  |
| Memory                       | Battery Backup                        |                           |               |               |               |                           |               |               |  |
| Mounting                     | Hang type or Wall Mould Type          |                           |               |               |               |                           |               |               |  |
| Display Format               | 24 Hour                               |                           |               |               |               |                           |               |               |  |
| Format                       |                                       | HH.MM                     |               |               |               |                           |               |               |  |
| Accuracy                     | + - 2 Minute / Year                   |                           |               |               |               |                           |               |               |  |
| Setting                      | IR Remote Controller up to 20 feet    |                           |               |               |               |                           |               |               |  |
| Dimension ± 5mm<br>Unit = mm | H130xW280xD49                         | H130xW280xD49             | H150xW292xD76 | H150xW412xD76 | H173XW412XD49 | H203XW614XD49             | H195XW433XD76 | H195XW553XD76 |  |