

Tel : 603-42949749

Fax : 603-42949759

www.lptech.com.my

LP 5 Row Digital Counter



BENEFIT:

- : Promotes Healthy Team (Line) Competition or Awareness
- : Indicates Corrective Action Needs.
- : Motivate Staff & Improve Productivity.
- : Real Time Production Information for supervisor & Manager.

FEATURES:

- : Large & Accurate Super Bright Led Display .
- : Low Maintenance

APPLICATION:

- : Production Planning & Control.
- : Production Status.

Specification

No. of Row	5
Digits Height	2.3", 4", 6", 8" and Others
Viewing Distance	2.3" Solid Segment - 60' / 80'
Recomented / Maximum	4" Solid Segment - 100' / 140' 6" Discrete - 180' / 240' 8" Discrete - 240' / 320'
Digits	2, 3, 4, 5, 6
Sided of Display	Single Sided or Double Sided
Power Source	240VAC or 110VAC + 10% 50 Hz
Memory	Non-volatile memory
Mounting	Hang or wall Type
Count Input	a - Edge Trigger NPN (Transistor Input) b - Relay, Microswitch etc.
Reset	Remote Reset
Setting	Infrared Remote control up to 20 feet
Option 1	RS232, RS485 Communication
Option 2	Break Time Setting

Single Sided	Dimension (mm) \pm 10%			
Model	Led Height	Length	Width	Height
LP5000-24-S-5	2.3"	418	49	327
LP5000-44-S-5	4"	640	49	495

HOW TO ORDER PRODUCTION COUNTER

LP5000-AB-CD-E

	Description	Choices
A	Digits Height	2= 2.3" (Solid Digits) 4= 4" (Solid Digits) 6= 6" (Discrete Digits) 8= 8" (Discrete Digits) O= Others
B	Number of digits	2, 3, 4, 5, 6
C	Sided of display	D : Double sided S : Single Sided
D	Display Colour	RED (Standard) G= Green A= Amber (Discrete only)
E	Line Description	1=TARGET 2=PLAN 3=ACTUAL 4=DIFFERENCE 5=OTHERS

OPERATION

- : TARGET : Preset by remote control
- : PLAN : Tact Time (Auto increment depend on tact time setting
max 9999 sec per count)
- : ACTUAL : The display will increment depend on the sensor input
- : DIFF : Automatic calculate base on ACTUAL - PLAN

We also provide customer with solutions and a variety of customize products Which meet your requirements economically.

Please Feel Free to contact us if you have any doubt?