



Tel : 603-42949749  
 Fax : 603-42949759  
[www.lptech.com.my](http://www.lptech.com.my)

## LP Analog Digital Display



### BENEFIT:

- : Promotes Healthy Team (Line) Competition or Awareness
- : Indicates Corrective Action Needs.
- : Motivate Staff & Improve Productivity.
- : Real Time Production Information for supervisor & Manager.

### FEATURES:

- : Large & Accurate Super Bright Led Display .
- : Low Maintenance

### APPLICATION:

- : Production Planning & Control.
- : Production Status.
- : Super Bright Led.

### Specification

No. of Row	1
Digits Height	2.3", 4", 6", 8" and Others
Viewing Distance	2.3" Solid Segment - 60' / 80'
Recomented / Maximum	4" Solid Segment - 100' / 140' 6" Discrete - 180' / 240' 8" Discrete - 240' / 320'
Digits	3, 4, 5
Sided of Display	Single Sided or Double Sided
Input Ranges	
Voltage Input	0 - 5V, 0 - 10V
Current Input	0 -20mA, 4 - 20mA
Power Source	240VAC or 110VAC $\pm$ 10% 50 Hz
Mounting	Hang or wall Type

### HOW TO ORDER

LPA1000-AB-CD

Key	Description	Choices
A	Digits Height	2= 2.3" (Solid Digits) 4= 4" (Solid Digits) 6= 6" (Discrete Digits) 8= 8" (Discrete Digits) 0= Others
B	Number of digits	2, 3, 4, 5, 6
C	Sided of display	D : Double sided S : Single Sided
D	Display Colour	R= RED ( Standard ) G= Green A= Amber ( Discrete only )

Eg : Require 4" led 3 digits, Single sided Red Color

**Model : LPA1000-43-SR**

**We also provide customer with solutions and a variety of customize products  
 Which meet your requirements economically.**

**Please Feel Free to contact us if you have any doubt?**



Tel : 603-42949749

Fax : 603-42949759

[www.lptech.com.my](http://www.lptech.com.my)

Release : 07/11

Drawing Name : LP Analogue Display-D7

## LP Single Row 4-20mA Digital Display



### Specification

Model	LPA1000-43-DR	LPA1000-44-DR	LPA1000-45-DR	LPA1000-43-SR	LPA1000-44-SR	LPA1000-45-SR	LPA1000-23-DR	LPA1000-24-DR	LPA1000-25-DR	LPA1000-23-SR	LPA1000-24-SR	LPA1000-25-SR
Display	Indoor Display											
No of row	1											
Segment	Solid 7 Segment Display											
Figure size	4 inch						2.3 inch					
Digits	3	4	5	3	4	5	3	4	5	3	4	5
Color of LED	Red											
Sided of display	Double Sided			Single Sided			Double Sided			Single Sided		
Input	4-20mA											
Setting	Remote controller up to 20 feet											
Visibility	4" up to 50 Meter						2.3" up to 25 Meter					
Power source	100 -240VAC $\pm$ 10% , 0.5A ,50 - 60 Hz ( 12v 1.5A Adaptor )											
Mounting	Hang type or Wall Mould Type											
Dimension $\pm$ 5mm Unit = mm	H195xW350xD76	H195xW430xD76	H195xW525xD76	H179xW 326xD49	H179xW412xD49	H179xW510xD49	H146xW220xD76	H146xW270xD76	H146xW316xD76	H124xW220xD49	H124xW246xD49	H124xW300xD49

We Also Provide Customer With Solutions And A Variety Of Customize Product Which Meet Their Requirement Economically.

## LP Single Row 4-20mA Digital Display



### Specification

Model	LPA1000-63-DR	LPA1000-64-DR	LPA1000-65-DR	LPA1000-63-SR	LPA1000-64-SR	LPA1000-65-SR	LPA1000-83-DR	LPA1000-84-DR	LPA1000-85-DR	LPA1000-83-SR	LPA1000-84-SR	LPA1000-85-SR
Display	Indoor Display											
No of row	1											
Segment	Discrete 7 Segment Display											
Figure size	6						8					
Digits	3	4	5	3	4	5	3	4	5	3	4	5
Color of LED	Red											
Sided of display	Double Sided			Single Sided			Double Sided			Single Sided		
Input	4-20mA											
Setting	Remote controller up to 20 feet											
Visibility	180 /240'						240 /320'					
Power source	100 -240VAC $\pm$ 10% , 0.5A ,50 - 60 Hz ( 12v 1.5A Adaptor )											
Mounting	Hang type											
Dimension $\pm$ 5mm Unit = mm	H255xW425xD76	H255xW545xD76	H255xW665xD76	H233xW425xD49	H233xW545xD49	H233xW665xD49	H317xW553xD76	H317xW713xD76	H317xW873xD76	H295xW531xD49	H295xW691xD49	H295xW851xD49

We Also Provide Customer With Solutions And A Variety Of Customize Product Which Meet Their Requirement Economically.